

# Edge Device TX2 Model



<b>CSA Certification</b>	Class I, Division 1, Groups C, D: T3 Ex ia IIB T3 Ga Class I, Zone 0, AEx ia IIB T3 Ga IP 66, Type 4X
<b>Operating Temperature</b>	-40° to 158°F (-40° to 70°C)
<b>Battery</b>	6 V, 2.5 Ah sealed lead acid Air-transportable DOT 49 CFR 173.159(d) exempt
<b>Solar Panel</b>	Integrated 1.5 W with optional 3 W external
<b>Global Positioning (GNSS) Receiver</b>	GPS, GLONASS, BeiDou, Galileo
<b>Local Wireless Connectivity</b>	Integrated Bluetooth Low Energy
<b>Cellular Connectivity</b>	Integrated LTE modem  North American modem (TX2x-NALx models) HSPA Bands: 2, 4, 5 LTE Bands: 2, 4, 5, 12-14, 66, 71  Global modem (TX2x-GOLx models) HSPA Bands: 1, 2, 4-6, 8, 19 LTE Bands: 1-5, 7-9, 12-14, 18-20, 25, 26, 28
<b>Antenna</b>	Integrated omnidirectional or external
<b>Size (diameter)</b>	4.0 in (10.1 cm)
<b>Size (length)</b>	9.0 in (23.0 cm)
<b>Weight</b>	3.0 lbs (1.4 kg)
<b>Compatible With</b>	All TOKU sensors

**Canada**  
333 96 Avenue NE  
Suite 5213  
Calgary, Alberta, T3K 0S3

**USA**  
2002 Timberloch Place  
Suite 200  
The Woodlands, Texas, 77380

[www.tokusystems.com](http://www.tokusystems.com)  
1-855-462-8658  
[sales@tokusystems.com](mailto:sales@tokusystems.com)



**TOKU**